

# Weighing Scales





# ABS "WEIGHT ONLY" SCALES

Capacity / Accuracy:
PS-50: 3 kg - 0,5 g / 6 kg - 1 g / 15 kg - 2 g.
PS-50 M: 3 kg - 1 g / 6 kg - 2 g / 15 kg - 5 g.
PS-60: 3 kg - 1 g / 6 kg - 2 g / 15 kg - 5 g.

New	odels
<b>PS-50</b>	
<b>PS-50</b>	Μ
<b>PS-60</b>	

- Back-light LCD display (5 digits 25 mm high) in PS-50 M model and LED in PS-60.
- PS-60 model has protection against humidity.
- Functions: weight, unit conversion, auto power off.
- Power: AC adapter (9V/800mA), internal rechargeable battery (6V/4Ah).
- Dimensions: 235 x 240 mm; plate (stainless steel): 230 x 190 mm (width x lenght).
- CE Approval (PS-50 M).

#### STAINLESS STEEL "WEIGHT ONLY" SCALES

- Capacity / Accuracy: 6 kg 2 g / 15 kg 5 g.
- Stainless steel housing and plate.
- LCD backlight display, with 25 mm digits.
- Functions: Tare, unit conversion (kg/lb), auto-off.
- Protection equivalent to IP-67.
- Internal rechargeable battery. Range: up to 300 hours, (depending on use conditions).
- Dimensions: 230 x 300 mm; plate: 230 x 190 mm (width x lenght).







### STAINLESS STEEL "WEIGHT ONLY" SCALES

• Capacity / Accuracy: 10 kg - 2 g.



- Stainless steel housing and plate.LCD backlight display, with 17 mm digits.
- Tare, unit conversion (kg/lb), auto-off and checkweigher (under-over) with alarm.
- RS-232 communications.
- Power: AC adapter, internal rechargeable battery.

Range: up to 100 hours (depending on use conditions).

• Dimensions: 240 x 200 mm; plate: 240 x 200 mm (width x lenght).

### **Price Computing Scales**



#### **ABS PRICE-COMPUTING SCALES**

- Capacity / Accuracy:
  - 6 kg 2 g, 15 kg 5 g or 30 kg 10 g.
- 3 backlight LCD displays in vendor side and 3 in buyer side. 5 digits 20 mm high.
- 20 key embossed membrane keyboard.
- Stainless steel pan and dust cover.
- Power: AC adapter (9V/800mA), internal rechargeable battery (6V/4Ah). Range: up to 90 hours (depending on use conditions).
- Dimensions: 315 x 330 mm; plate: 300 x 230 mm (width x lenght).

**SC-100** 

• CE approval.

#### STAINLESS STEEL PRICE-COMPUTING SCALES

• Capacity / Accuracy:

20 kg - 5 g.

- Formats: Flat and Tower.
- Stainless steel housing and plate.
- Double LCD back-light display (frontal/back), with 13 mm digits (for weight/amount) and 12 mm (for price).
- 100 PLUs, 8 presets.
- Functions: Fix price, tare and auto-off.
- Power: Mains and internal rechargeable battery.
   Range: up to 30 hours (depending on use conditions).
- Dimensions: 305 x 290 mm; plate: 305 x 220 mm (width x lenght).
- CE approval.



SPC

## **Other Industrial Scales**

#### **ABS PRECISION SCALES**



- Capacity / Accuracy: **PB-60** 300 g - 0,005 g / 600 g - 0,01 g /
- 1.500 g 0,02 g / 3.000 g 0,05 g.
- Back-light LCD display.
  6 digits 15 mm high.
- Functions: piece counting,

percent weighing, accumulation, unit conversion.

- Power: AC adapter (9V/800mA), internal rechargeable battery.
- Stainless steel plate.
- Wind shield included in 300 and 600 g models.
- Dimensions: 190 x 220 mm (width x lenght).

#### **ABS PIECE-COUNTING SCALES**

- Capacity / Accuracy: 3 kg - 0,1 g / 6 kg - 0,2 g /
- 15 kg 0,5 g / 30 kg 1 g. • Internal resolution: 1/60.000.
- Internal resolution: 1/60.000.
- 3 LCD back-light displays. 6 digits 20 mm high.
- Functions: piece counting, preset tares, pieces checking with alarm, accumulation.
- Power: AC adapter (9V/800mA), internal rechargeable battery.
- Dimensions: 315 x 330 mm;

plate (stainless steel): 300 x 230 mm (width x lenght).



### DIBAL, S.A.

Astintze, 24 (Pol. Ind. Neinver) - 48160 Derio - Vizcaya (SPAIN) Tel.: (+34) 94 452 15 10 - Fax: (+34) 94 452 36 58 - www.dibal.com - dibal@dibal.com

PC-50